

AVAILABLE SENSOR RATINGS AND PART NUMBERS

<u>BREAKER TYPE</u>	<u>FRAME SIZE (AMPS)</u>	<u>SENSOR RATING (AMPS)</u>	<u>PART NUMBER</u>
DS-206 & DSL-206 ↓ ↓	800	100	44050-036-01
	800	150	-02
	800	200	-03
	800	300	-04
	800	400	-05
	800	600	-06
	800	800	-07
DS-416 & DSL-416 ↓ ↓	1600	100	-01
	1600	150	-02
	1600	200	-03
	1600	300	-04
	1600	400	-05
	1600	600	-06
	1600	800	-07
	1600	1200	-08
	1600	1600	-09
DS-420	2000	2000	-10
DS-632 ↓	3200	2400 (Neutral)	-11
	3200	2400 (Main Phase)	-12
	3200	3200 (Neutral)	-13
	3200	3200 (Main Phase)	-14
DS-840	4000	4000	-15

For dimensions see drawing no. B44050-036.

NOTE: The continuous rating of any type DS/DSL breaker is limited to 125% of the sensor rating, or the frame size current rating, whichever is the lesser.

REV.						C.R.						DATE						BY									
STANDARD TOLERANCE UNLESS OTHERWISE SPECIFIED								LINEAL DIM.				TWO PLACE DECIMAL ± .000 THREE PLACE DECIMAL ± .000															
								HOLE DIA.				FRACTIONAL, LETTER, OR NUMBERED DRILL + .004 THREE PLACE DECIMAL ± .002 - .003															
								ANGLE				DIMENSIONED ± 1° UNDIMENSIONED 90° ± 5°															
SCALE				DRAWN GH				CHRD.				DATE 5-18-77				G.S. <i>SWS</i> 5-C13				 SQUARE D COMPANY BARKELEW PLANT MIDDLETOWN, OHIO USA							
TITLE AVAILABLE SENSOR RATINGS &																											
PART NUMBERS																											
PRINTS TO												<i>PBD-40052</i>															
A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	R	S	T	U	V	W	X	Y	Z		